

## **Customer Specification**

## **PART NO. 22RC2S06**

#### Construction

						Diameter ("in")	
1) Component 1						2 x 1 COND	
a) Conductor						22 (19/34) AWG SPC	0.032
b) Insulation						0.009" Wall, Nom. PTFE	0.050
(1) Colo	or(s)						
Cond	Color	Cond	Color	Cond	Color	_	
1	WHITE	2	WHITE/BLUE				
2) Cable Assembly						2 Components Cabled	
a) Twists						8.0 twists/ft. (min.)	
3) Shield						SPC BRAID Shield, 85% Coverage (min.)	
4) Jacket						0.010" Wall, Nom., PTFE Tape	0.138 (0.145 max.)
a) Color(s)						WHITE	

### **Applicable Specifications**

1) Other		
a) Component 1	SAE-AS22759/11	
b) Overall	NEMA WC27500 Type RC	
2) CE	EU Low Voltage Directive 2006/95/EC	

#### **Environmental**

1) CE: EU Directive 2011/65/EU(RoHS2)	
	This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011. No Exemptions are required for RoHS Compliance on this item. Refer to the <u>RoHS Certificate of compliance</u> for more detail.
2) REACH Regulation (EC 1907/2006)	
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see <u>Alpha's REACH SVHC Declaration</u> .

#### **Properties**

Physical & Mechanical Properties				
-55 to 200°C				
10X Cable Diameter				
11.8 lbs. max.				
Engineering purposes only				
600 V <sub>RMS</sub>				
27 pf/ft. @1 kHz, Nominal Conductor-to-Conductor				
49 pf/ft. @1 kHz, Nominal				
55 ω				
0.17 μH/ft., Nominal				
14.1 ω/1000ft. @20°C, Nominal				
-	10X Cable Diameter   11.8 lbs. max.   Engineering purposes only   600 V <sub>RMS</sub> 27 pf/ft. @1 kHz, Nominal Conductor-to-Conductor   49 pf/ft. @1 kHz, Nominal   55 ω   0.17 µH/ft., Nominal			

### Other

Packaging	Flange x Traverse x Barrel (inches)	
a) 100 FT	6.5 x 2 x 1.9 Continuous length	
b) Bulk(Made-to-order)	Quantity = 2500 ft.: 8 pieces maximum, 100 ft. min length Quantity 2500="" ft.:="" 5="" pieces="" maximum,="" 100="" ft.="" min="" length="">	
	[Spool dimensions may vary slightly]	

#### www.alphawire.com

Alpha Wire 2200 US Highway 27 South Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

💋 AlphaWire

# **EU/UK/China ROHS CERTIFICATE OF COMPLIANCE**

To Whom It May Concern:

Alpha Wire Part Number: 22RC2S06

22RC2S06, RoHS-Compliant Commencing With 7/1/2005 Production

#### Note: all colors and put-ups

This document certifies that the Alpha part number cited above, including all packaging materials, is manufactured in accordance with Directive 2011/65/EU of the European Parliament, better known as the RoHS Directive (commonly known as RoHS 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. This certification extends to amending Directive 2015/863/EU which expanded the list of restricted substances to 10 items (commonly known as RoHS 3). This product also complies with UK - RoHS. The reader is referred to these Directives for the specific definitions and extents of the Directives. **No Exemptions are required for RoHS Compliance on this item**. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS 2 per GB/T 26572-2011.

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm )
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) ,	
Including Deca-BDE	0.1% by weight (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	0.1% by weight (1000 ppm)
Butyl benzyl phthalate (BBP)	0.1% by weight (1000 ppm)
Dibutyl phthalate (DBP)	0.1% by weight (1000 ppm)
Diisobutyl phthalate (DIBP)	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire:

Dave Watson, Director of Engineering 3/31/2025

Alpha Wire 2200 US Highway 27 South Richmond, IN 47374 Tel: 1-908-925-8000