

Customer Specification

PART NO. 805062W

Construction

1) Construction	
a) Material	Polyester, high tenacity, continuous filament
b) Type	II
c) Size	3
d) Finish	B – Microcrystalline fungicide wax, mercury and copper free
e) Dimensions	0.085 +/- 0.009" x 0.014 +/- 0.003"
f) Color	White

Applicable Specifications

1) Other	A-A-52081-B-3	
	FED-STD-191	

Environmental

--

1) EU Directive 2011/65/EU(RoHS2):	
	All materials used in the manufacture of this part meet the requirements of European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for RoHS C of C .
2) REACH Regulation (EC 1907/2006):	
	This product does not contain any of the 16 substances listed on the European Union's REACH Substance of Very High Concern (SVHC) candidate list in excess of 0.1% mass of the item.
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

Properties

a) Breaking Strength	50 Lbs. Min.
b) Elongation	40% Max.
c) Finish Weight	15% - 32%
d) Temperature Range	-73°C to 177°C

Other

--

1) Standard Packaging	
a) 500 Yard Spools	Cardboard Tubes
b) Length Tolerance	+ 10/-3%
c) Multiple Lengths	4 lengths max per tube
	50 yard minimum individual length

www.alphawire.com

Alpha Wire
2200 US Highway 27 South
Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

SpecPDFFooterConfidential

[illegible]

□□□□

Lead

Mercury

Cadmium

Hexavalent Chromium

Polybrominated Biphenyls (PBB)

Polybrominated Diphenyl Ethers (PBDE),

Including Deca-BDE

Bis(2-ethylhexyl) phthalate (DEHP)

Butyl benzyl phthalate (BBP)

Dibutyl phthalate (DBP)

Diisobutyl phthalate (DIBP)

□ □ □ □ □

□□□□□□□□0.1% (1000 ppm)

□□□□□□□□0.1% (1000 ppm)

□□□□□□□□0.01% (100 ppm)

□□□□□□□□0.1% (1000 ppm)

□□□□□□□□0.1% (1000 ppm)

□□□□□□□□0.1% (1000 ppm)

□□□□□□□□0.1% (1000 ppm)

□□□□□□□□0.1% (1000 ppm)

0.1% (1000 ppm)

□□□□□□□□0.1% (1000 ppm)

Alpha Wire

Alpha Wire □□□□□□□□

DeBW

