

# Customer Specification

## PART NO. 85245CY

### Construction

|                      |        |      |        |      |                | Diameters (In)  |                |
|----------------------|--------|------|--------|------|----------------|---|----------------|
| 1) Component 1       |        |      |        |      |                | 1 X 5 COND  |                |
| a) Conductor         |        |      |        |      |                | 24 (19/36) AWG Bare Copper  | 0.025          |
| b) Insulation        |        |      |        |      |                | 0.022" Wall, Nom. PVC   | 0.069          |
| (1) Print            |        |      |        |      |                | ALPHANUMERIC NUMBERS - 1-ONE ALTERNATING AND INVERTED   |                |
| (2) Color(s)         |        |      |        |      |                |   |                |
| Cond                 | Color  | Cond | Color  | Cond | Color          |   |                |
| 1                    | RED #1 | 3    | RED #3 | 5    | YELLOW/GREEN/C |   |                |
| 2                    | RED #2 | 4    | RED #4 |      |                |   |                |
| c) Cabling           |        |      |        |      |                | 5 COND Cabled   |                |
| (1) Twists:          |        |      |        |      |                | 6.9 Twists/foot (min)   |                |
| (2) Orientation:     |        |      |        |      |                | Components to be arranged from INSIDE LAYER to OUTSIDE LAYER  |                |
| (3) Core Wrap        |        |      |        |      |                | REMAI Tape, 25% Overlap, Min.   |                |
| d) Jacket            |        |      |        |      |                | 0.020" Wall, Nom.,PVC, Oil Resistant  | 0.252+/- 0.017 |
| (1) Color(s)         |        |      |        |      |                | BLACK   |                |
| (2) Jacket Separator |        |      |        |      |                | Tissue Tape, 25% Overlap, Min.  |                |
| 2) Shield            |        |      |        |      |                | Tinned Copper BRAID Shield,85% Coverage, Nom.   |                |
| 3) Jacket            |        |      |        |      |                | 0.040" Wall, Nom.,PVC, Oil Resistant  | 0.360+/- 0.025 |
| a) Color(s)          |        |      |        |      |                | BLACK   |                |
| b) Jacket Separator  |        |      |        |      |                | Tissue Tape, 20% Overlap, Min.  |                |
| c) Print             |        |      |        |      |                | ALPHA WIRE-* P/N 85245CY 5C 24 AWG<br>XTRAGUARD(R) CONTINUOUS FLEX CONTROL CABLE<br>RU AWM 2587 CONSTANT FLEXING OR CRU<br>AWM I/II A/B FT1 90C 600V<br>CE ROHS (SEQ FOOTAGE)<br>* = Factory Code |                |

### Applicable Specifications

|  |  |
|--|--|
|  |  |
|--|--|

|                      |                                     |                             |
|----------------------|-------------------------------------|-----------------------------|
| 1) UL                |                                     |                             |
| a) Component 1       | AWM/STYLE 10012                     | 90°C / 600 V <sub>RMS</sub> |
| b) Overall           | AWM/STYLE 2587                      | 90°C / 600 V <sub>RMS</sub> |
| 2) CSA International | C(RU) AWM I/II A/B                  | 90°C / 600 V <sub>RMS</sub> |
|                      | FT1                                 |                             |
| 3) Other             | VDE 0472, Section 803 Oil Test      |                             |
| 4) CE:               | EU Low Voltage Directive 2014/35/EU |                             |

## Environmental

|  |   |
|--|---|
| 1) CE: EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3): |   |
|  | This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011 and the amending Directive 2015/863/EU of 4 June 2015 . No Exemptions are required for RoHS Compliance on this item. |
| 2) REACH Regulation (EC 1907/2006):                                      |   |
|  | This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.  |
| 3) California Proposition 65:  |   |
|  | This product may contain substances known to the State of California to cause Cancer or Reproductive Harm, but is exempt from labeling based on the Consent Judgement. See the Alpha Wire website for more information.                                     |

## Properties

| <b>Physical &amp; Mechanical Properties</b>                  |   |
|--|---|
| 1) Temperature Range   | -40 to 90°C(static), -5 to 90°C (dynamic)             |
| 2) Bend Radius   | 8X Cable Diameter(static), 8X Cable Diameter(dynamic) |
| 3) Pull Tension  | 25 Lbs, Maximum                                       |
| <b>Electrical Properties</b> (For Engineering purposes only) |   |
| 1) Voltage Rating  | 600 V <sub>RMS</sub>                                  |
| 2) Capacitance   | 28 pF/ft @1 kHz, Nominal Conductor to Conductor       |
| 3) Ground Capacitance  | 50 pF/ft @1 kHz, Nominal                              |
| 4) Inductance  | 0.24 μH/ft, Nominal                                   |
| 5) Conductor DCR   | 22.3 Ω/1000ft @20°C, Nominal                          |
| 6) OA Shield DCR   | 3.5 Ω/1000ft @20°C, Nominal                           |

## Other

|  |
|--|
|  |
|--|

| <b>Packaging</b> | Flange x Traverse x Barrel (inches)         |
|------------------|---|
| a) 1000 FT       | 18 x 14.25 x 8 Continuous length            |
| b) 500 FT        | 13.5 x 10 x 4 Continuous length             |
| c) 100 FT        | 12 x 5.94 x 5 Continuous length             |
|                  | <i>[Spool dimensions may vary slightly]</i> |
|                  |   |

[www.alphawire.com](http://www.alphawire.com)

Alpha Wire  
2200 US Highway 27 South  
Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. <br /> <br />  
©2019 ALPHA WIRE - all rights reserved.



