

# **Customer Specification**

## **PART NO. AZ181930**

### Construction

|  | Diameters (In)               |                |
|--|------------------------------|----------------|
| 1) Component 1   | 1 X 1 HOOKUP                 |                |
| a) Conductor   | 18 (19/30) AWG Tinned Copper | 0.048          |
| b) Insulation  | 0.0115" Wall, Nom. ETFE      | 0.071+/- 0.002 |
| (1) Color(s) WHITE, BLACK, RED, GREEN, YELLOW, BLUE, BROWN ORANGE, SLATE, VIOLET |                              |                |

# **Applicable Specifications**

| 1) Other | SAE-AS22759/16 | 150°C / 600 V <sub>RMS</sub> |
|----------|----------------|------------------------------|
|          |                |                              |

### **Environmental**

| 1) EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3): |  |
|--|--|
|  | All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU and the amending Directive 2015/863/EU of 4 June 2015 regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. |
| 2) REACH Regulation (EC 1907/2006):                                  |  |
|  | This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.   |
| 3) California Proposition 65:  | This product may contain substances known to the State of California to cause Cancer or Reproductive Harm, but is exempt from labeling based on the Consent Judgement. See the Alpha Wire website for more information.  |

### **Properties**

| Physical & Mechanical Properties |                                 |  |
|----------------------------------|---------------------------------|--|
| 1) Temperature Range             | -55 to 150°C                    |  |
| 2) Bend Radius                   | 10X Cable Diameter              |  |
| 3) Pull Tension                  | 14.9 Lbs, Maximum               |  |
| Electrical Properties            | (For Engineering purposes only) |  |
| 1) Voltage Rating                | 600 V <sub>RMS</sub>            |  |
| 2) Inductance                    | 0.04 μH/ft, Nominal             |  |
| 3) Conductor DCR                 | 5.9 Ω/1000ft @20°C, Nominal     |  |
|                                  |                                 |  |

#### **Other**

| Packaging   | Flange x Traverse x Barrel (inches)  |
|---|--------------------------------------|
| a) 1000 FT  | 6.5 x 4 x 2.5 Continuous length      |
| b) 500 FT   | 6.5 x 2 x 1.9 Continuous length      |
| c) 100 FT   | 2.75 x 2 x 1.125 Continuous length   |
| d) Bulk(Made-to-order)  |                                      |
|   | [Spool dimensions may vary slightly] |
| Notes:  |                                      |
| a) Certain colors and put-up combinations may only be available by special order, minimums may apply. |                                      |

#### www.alphawire.com

Alpha Wire 2200 US Highway 27 South Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. <br/>
consent of ALPHA WIRE - all rights reserved.



Alpha Wire □□□□AZ181930

AZ181930000RoHS0000 2005/7/1 000000

Lead Mercury □□□□□□□□0.1% (1000 ppm) Cadmium Hexavalent Chromium □□□□□□□□0.1% (1000 ppm) Polybrominated Biphenyls (PBB) □□□□□□□□0.1% (1000 ppm) Polybrominated Diphenyl Ethers (PBDE), □□□□□□□□0.1% (1000 ppm) Including Deca-BDE Bis(2-ethylhexyl) phthalate (DEHP) Butyl benzyl phthalate (BBP) Dibutyl phthalate (DBP) □□□□□□□□0.1% (1000 ppm) Diisobutyl phthalate (DIBP)

Alpha Wire DDDDDDDDD

ППППППП Dave Watson 2025/3/31